

AGRI TRAILER - Data Sheet



Description

AGRI TRAILER has been specially designed for tractor trailers. It is the ideal tire for modern farming, suitable for transport applications both on and off the road. Its robust construction results in high load capacity, whereas its extra-deep tread allows for a better mileage and a longer service life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
10.00 - 20	STANDARD	94050352	18	7.5	7.0 ; 8.0	11.3	42.5	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..