

AGRIFORCE BK T71 - Technical Specifications



Description

AGRIFORCE BK T71 is BKT's brand-new rubber track series for high-power tractors employed in general tillage and row crop applications. The tread is made of a high-performance compound that ensures maximum resistance against cuts, tears, and abrasion. The optimized tread pattern provides excellent traction and ride comfort, whereas the drive lugs of the positive drive system have an optimized shape for best flexibility. In addition, the track carcass has been reinforced with four layers of high-tensile steel cords. As a result, AGRIFORCE BK T71 offers the perfect balance of high dimensional stability and flexibility to ensure extraordinary durability in all seasons. Farming tracks have no metal core, a feature that improves flexibility especially on wet and soft soil. The overall advantages of rubber tracks are enhanced productivity and performance since track-driven tractors can run at higher speeds on field at the same power and show improved fuel efficiency.

UM

Metric Units

Drive type

POSITIVE

Machinery

Agriculture: High-Power Tractor

Tyre Size

18" x 6 " x 53

Track Width

457

Track Length

8077.2

Tread Lugs

106

Tread Lugs Height

51

Pitch

152.4

Guide Lugs

-

Drive Lugs

53

Carcass Plies

3

Carcass Main Cable Size

5.2

Carcass Thickness

35

Track Weight

332

Printed on 07/05/2024 07:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..