

AGRIFORCE BK T71 - Technical Specifications



Description

AGRIFORCE BK T71 is BKT's brand-new rubber track series for high-power tractors employed in general tillage and row crop applications. The tread is made of a high-performance compound that ensures maximum resistance against cuts, tears, and abrasion. The optimized tread pattern provides excellent traction and ride comfort, whereas the drive lugs of the positive drive system have an optimized shape for best flexibility. In addition, the track carcass has been reinforced with four layers of high-tensile steel cords. As a result, AGRIFORCE BK T71 offers the perfect balance of high-dimensional stability and flexibility to ensure extraordinary durability in all seasons. Farming tracks have no metal core, a feature that improves flexibility especially on wet and soft soil. The overall advantages of rubber tracks are enhanced productivity and performance since track-driven tractors can run at higher speeds on field at the same power and show improved fuel efficiency.

UM

Imperial

Drive type

POSITIVE

Machinery

Agriculture: High-Power Tractor

Tyre Size

18" x 6" x 54

Track Width

18

Track Length

324

Tread Lugs

108

Tread Lugs Height

2

Pitch

6

Guide Lugs

-

Drive Lugs

54

Carcass Plies

3

Carcass Main Cable Size

0.2

Carcass Thickness

1.4

Track Weight

745

Printed on 27/04/2024 08:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..