

## AGRIMAX ELOS - Data Sheet



### Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Tractor

| SIZE                                     | Version  | TRA Code | LI/SS        | RIM REC | RIM ALT                                                         | SW  | OD   | SLR | RC   | SRI | Type | ECE              |
|------------------------------------------|----------|----------|--------------|---------|-----------------------------------------------------------------|-----|------|-----|------|-----|------|------------------|
| <b>420/85 R 28</b><br><b>(16.9 R 28)</b> | STANDARD | R2       | 139 A8/B     | W 15 L  | W 13 ; W 14 L                                                   | 438 | 1467 | 665 | 4349 | 700 | TL   | E4-106R-000768   |
| <b>480/70 R 34</b>                       | STANDARD | R2       | 155 A8/155 B | W 15 L  | W 16 L ; W 14 L                                                 | 500 | 1605 | 733 | 4868 | 750 | TL   | E11-106R-007532  |
| <b>340/85 R 38</b><br><b>(13.6 R 38)</b> | STANDARD | R2       | 133 A8/B     | W 12    | W 11                                                            | 353 | 1602 | 735 | 4774 | 775 | TL   | E4-106R-001477   |
| <b>380/85 R 38</b><br><b>(14.9 R 38)</b> | STANDARD | R2       | 139 A8/B     | W 12    | W 11 ; W 13                                                     | 380 | 1662 | 772 | 4994 | 775 | TL   | E4-106R-000779   |
| <b>420/85 R 38</b><br><b>(16.9 R 38)</b> | STANDARD | R2       | 144 A8/B     | W 15 L  | W 13 ; W 14 L                                                   | 438 | 1735 | 785 | 5135 | 825 | TL   | E4-106R-000780   |
| <b>480/80 R 38</b><br><b>(18.4 R 38)</b> | STANDARD | R2       | 149 A8/B     | W 16 L  | W 15 L ; DW 16 L                                                | 489 | 1803 | 821 | 5356 | 825 | TL   | E11-106R-002991  |
| <b>710/70 R 38</b>                       | STANDARD | R2       | 178 A8/B     | DW 23 B | DW 25 B                                                         | 716 | 2019 | 915 | 6103 | 925 | TL   | E11-106R-004896  |
| <b>480/80 R 42</b><br><b>(18.4 R 42)</b> | STANDARD | R2       | 151 A8/B     | DW 16 L | DD 16 L ; W 16 L                                                | 489 | 1890 | 857 | 5629 | 875 | TL   | E4-106R-001481   |
| <b>520/85 R 42</b><br><b>(20.8 R 42)</b> | STANDARD | R2       | 167A8/B      | DW 16 L | DD 18 L ; DW 18 L                                               | 516 | 1988 | 920 | 6095 | 925 | TL   | E11-106R-0010146 |
| <b>520/85 R 42</b><br><b>(20.8 R 42)</b> | STANDARD | R2       | 157 A8/B     | DW 16 L | DD 18 L ; DW 18 L                                               | 516 | 1988 | 904 | 5865 | 925 | TL   | E4-106R-000793   |
| <b>520/85 R 46</b>                       | STANDARD | R2       | 169 A8/169 B | DW 16 L | DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L | 530 | 2075 | 957 | 6293 | 975 | TL   | E11-106R-007935  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 01:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..