

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Туре	TL
Tyre Size	260/70 R 20
LI/SS	113 A8/B

Dimensions US Standard

Usa code	94044221
Section Width (inch)	10.2
Overall Diameter (inch)	34.3
Static Loaded Radius (inch)	15.8
Rolling Circumference (inch)	103.9
Rim Rec	W 8
Rim Alt	9;W9
ECE	E4-106R-000640
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 02:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..