

## AGRIMAX RT 765 - Technical Specifications



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	360/70 R 20
LI/SS	129 A8/B

Dimensions US Standard

Usa code	94021949
Section Width (inch)	14.1
Overall Diameter (inch)	41
Static Loaded Radius (inch)	18.5
Rolling Circumference (inch)	122.9
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E4-106R-000647
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1920	2200	2540	2850	3190	3520	3800	4080
25	1920	2200	2540	2850	3190	3520	3800	4080
20	2060	2360	2710	3060	3410	3760	4070	4360
5 LT	2580	2950	3390	3840	4270	4710	5090	5470
5 HT	2060	2360	2710	3060	3410	3760	4070	4360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 13:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..