

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	230/95 R 32 (9.5 R 32)
LI/SS	128 A8/B

Dimensions US Standard

Usa code	94026678
Section Width (inch)	9
Overall Diameter (inch)	49.3
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	150
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000764
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1550	2030	2470	2700	2870	3140	3420	3690	3960	-
25	1550	2030	2470	2700	2870	3140	3420	3690	3960	-
20	1660	2170	2650	2900	3060	3360	3660	3960	4250	-
5	1850	2330	2870	3390	3940	4060	4530	5000	5480	5950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 02:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..