

AGRIMAX SPARGO SB - Data Sheet



Description

AGRIMAX SPARGO SB is a special row crop tire that is particularly suitable for tractors and sprayers in open-field spraying and row crop applications, or for specialized tractors in orchards and vineyards. Thanks to its advanced VF-technology (Very Increased Flexion), the tire is able to carry 40% heavier load compared to a standard tire of the same size at the same inflation pressure. The wide footprint ensures uniform weight distribution as well as low soil compaction in the fields. AGRIMAX SPARGO SB stands for excellent performance and high speed-efficiency both on and off the road, up to 65 km/h. Moreover, the robust polyester casing provides improved durability, better handling and dimensional stability as well as enhanced equipment stability and control both in the fields and on the road, thus avoiding the risk of tire slippage and reducing fuel consumption. AGRIMAX SPARGO SB features a special sidewall design that provides tire flexibility and reduces vibrations - essential for operations with precision sprayers. Finally, the steel-belted construction guarantees excellent puncture resistance plus outstanding support of heavy loads, while the extraordinarily strong lug design stands for improved traction. The combination of all these features results in a lower economic and environmental impact, increasing productivity and operator comfort at the same time.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Tractor

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
VF 270/95 R 32	STEEL BELTED	94076352	148D	W9		11	52.7	24.3	160.6	TL	E11-106R-0010499
VF 420/85 R 34	STEEL BELTED	94513598	165D	DW 15 L	DW 14 L	16.9	62.1	28.2	188.1	TL	E11-106R-0010943
VF 270/95 R 36	STEEL BELTED	94511594	150D	W9		11	56.7	26.1	173.1	TL	E11-106R-0010612
VF 270/95 R 38	STEEL BELTED	94506309	151D	W9		11	58.7	27.2	179	TL	E11-106R-0010500
VF 380/95 R 38	STEEL BELTED	94513833	165D	W 13	W 12	15.6	66.5	30.2	201.4	TL	E11-106R-0010942
VF 380/90 R 46 CFO	STEEL BELTED	94076123	173D	W13	W12;DW13	15.7	72.9	33.7	223.1	TL	E11-106R-0010176
VF 270/95 R 48	STEEL BELTED	94076499	155D	W9		9.4	68.7	32.1	211.5	TL	E11-106R-0010463
VF 380/90 R 50 CFO	STEEL BELTED	94076116	175D	W13	W12;DW13	15.7	76.9	35.6	235.7	TL	E11-106R-0010177
VF 270/95 R 54	STEEL BELTED	94512898	157D	W9		11	74.8	35.2	230	TL	E11-106R-0010833
VF 320/90 R 54	STEEL BELTED	94513284	168D	W11	W10;DW10A;DW11	12.7	77.2	36.1	237.4	TL	E11-106R-0010834
VF 380/90 R 54	STEEL BELTED	94513260	176D	W13	W12;DW12;W13A;DW13;DW13A	15.6	81.1	37.7	248.4	TL	E11-106R-0010178

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..