

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 42
LI/SS	176 D

Dimensions US Standard

Usa code	94075317
Section Width (inch)	18.9
Overall Diameter (inch)	72.2
Static Loaded Radius (inch)	33
Rolling Circumference (inch)	219.4
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-009072
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52
45	8110	8980	9850	10280	10860	11150	11440	12020	12600	13030	13610	14050	14480
from 40 to 25	8770	9720	10640	11120	11740	12060	12370	12990	13630	14090	14720	15190	15660
20	8940	9910	10860	11350	11990	12310	12630	13250	13900	14390	15020	15500	15980
12	9120	10100	11070	11570	12220	12550	12870	13520	14170	14660	15300	15800	16290
5*	9650	10690	11710	12230	12920	13270	13610	14290	14980	15500	16190	16700	17220
Upto 20 Cyclic	9960	11030	12090	12610	13330	13690	14050	14750	15470	16000	16700	17240	17770
Upto 10 Cyclic	11890	13170	14420	15060	15920	16340	16770	17610	18470	19110	19940	20580	21220
Upto 5 Cyclic	13150	14570	15970	16680	17630	18090	18560	19490	20440	21150	22080	22790	23490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 12:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..