

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	HD
Type	TL
Tyre Size	1050/50 R 32 CHO
LI/SS	184 A8/181 B

Dimensions US Standard

Usa code	94076185
Section Width (inch)	41.7
Overall Diameter (inch)	74.5
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	223.8
Rim Rec	36.0 VA
ECE	E11-106R-0010258

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	8190	9280	11640	12920	14370	15460	16920	18190
25	8930	10120	12700	14090	15670	16860	18450	19840
20	9560	10840	13590	15080	16780	18050	19750	21230
10 Cyc	14740	16700	20950	23250	25870	27830	30460	32740
5 Cyc	16070	18220	22860	25360	28220	30360	33220	35710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..