

AS 2001 - Technical Specifications



Description

AS 2001 is a bias cross-ply tire which best suits tractors in soil tillage operations. Its design provides excellent traction and self-cleaning properties. AS 2001 is made of a special cut-and-chip resistant compound that also ensures great load capacity.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	134 A8

Dimensions US Standard

Usa code	94002702
Ply Rating	10
Section Width (inch)	16.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	170
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004344
TRA Code	R1

Load capacity (lbs)

mph / psi	28
25	4680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 09:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..