

AT 109 - Technical Specifications



Description

AT 109 is an all-terrain tire for ATVs. Its tread design provides excellent field protection.

UM

International Standard

Construction

🔅 BIAS

Machinery

Agriculture: ATV

| Version | STANDARD |
|-----------|-----------------|
| Туре | TL |
| Tyre Size | AT 145 / 70 - 6 |

Dimensions International Standard

| Ply Rating | 2 |
|-----------------------|-----|
| Section Width (mm) | 137 |
| Overall Diameter (mm) | 366 |
| Rim Rec | 4.5 |
| | |
| Load capacity (Kg) | |

| LOau | capaci | ιy | KG) | |
|------|--------|----|-----|--|
| | | | | |

| km/h / bar | 0.28 |
|------------|------|
| 80 | 35 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/06/2025 16:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..