

AT 109 - Data Sheet



Description

AT 109 is an all-terrain tire for ATVs. Its tread design provides excellent field protection.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: ATV

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 145 X 70 - 6	STANDARD	94000647	2	4.5		5.4	14.4	TL	
AT 16 X 8 - 7	STANDARD	94000661	2	6.5 AT	6.0 AT	7.2	16.5	TL	
AT 18 X 9.5 - 8	STANDARD	94000685	2	7.5 AT	8.0 AT	8.7	18.4	TL	E11-75R-004668
AT 20 X 7 - 8	STANDARD	94000692	2	5.5 AT	6.0 AT	6.7	19.8	TL	E11-75R-004669
AT 21 X 9 - 8	STANDARD	94000715	2	7.0 AT	6.5 AT ; 7.5 AT	8.7	21.1	TL	
AT 22 X 11 - 8	STANDARD	94000739	2	9.0 AT	8.5 AT	9.1	22.8	TL	E11-75R-004670
AT 25 X 12 - 9	STANDARD	94000753	2	9.5 AT	9.0 AT ; 10.0 AT	10.6	24.3	TL	E11-75R-004671

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 03:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..