

AT 316 - Data Sheet



Description

AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Compact Utility Tractor

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
24 X 12.00 - 12	ARAMID BELTED	6	10.50 I - 55 ; I - 70 ; I - 90		315	610	271	1769	TL	
24 X 12.00 - 12	STANDARD	4	10.50 I - 55 ; I - 70 ; I - 90		315	610	271	1769	TL	E11-106R-004082

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..