

## AW 909 - Technical Specifications



### Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	141 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	391
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E4-106R-001547

## Load capacity (Kg)

km/h / bar	3.60
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..