



## BK 823 - Data Sheet



### Description

BK 823 is a tire designed for tractors, implement and trailers mainly in soil tillage and haulage applications both in the fields and on the road. Its special block pattern makes the tire particularly suitable for heavy-duty service where excellent steering performance is required. An HD version is also available with improved cut and chip resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Tractor • Trailer

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	94049202	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-004338
9.00 - 16	STANDARD	94042432	124 A8	12	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003603
9.00 - 16	STANDARD	94040131	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003604
9.00 - 16	STANDARD	94060252	121 A8	10	6.5		9.6	35.1	15.5	101.7	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 01:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..