

## BK-LOADER 53 - Technical Specifications



### Description

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Loader

Version	ARAMID BELTED
Type	TL
Tyre Size	405/70 R 18
LI/SS	153A2/149A4

## Dimensions US Standard

Usa code	94069705
Section Width (inch)	16
Overall Diameter (inch)	41.1
Rim Rec	13
Rim Alt	14 ; 13 SDC; 12 ;12 SDC

## Load capacity (lbs)

mph / psi	22	29	36	44	51	58	65	73	80
12	2520	3230	3810	4380	5020	5530	6100	6600	7170
5	2830	3630	4270	4920	5640	6210	6850	7410	8050
STATIC	4520	5810	6850	7880	9030	9940	10970	11880	12900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..