

DON 2000 - Data Sheet



Description

DON 2000 is a suitable for transport operations with trailers and light trucks both on and off the road. It ensures extra durability along with high performance during the entire product life-cycle.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Light Truck • Trailer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
7.50 - 16	STANDARD	94013876	16	6.00 G	5.50 F	8.5	33.1	0	0	TT
10.00 - 20	INDUSTRIAL TRAILER	94040858	16	7.5	7.0 ; 8.0	11.3	42.5	0	0	TT
10.00 - 20	INDUSTRIAL TRAILER	94043866	18	7.5	7.0 ; 8.0	11.3	42.5	0	0	TT
11.00 - 20	STANDARD	94067725	18	8.0	7.5 ; 8.5	11.5	43.7	20.5	134.4	TT
12.00 - 20	STANDARD	94022540	18	8.5	8.0 ; 9.0	12.4	45.1	21.1	138.5	TT
9.00 - 20	STANDARD	94022571	16	7.0	6.5 ; 7.5	10.6	41.3	0	0	TT
9.00 - 20	TRACTOR TRAILER	94045495	16	7.0	6.5 ; 7.5	10.6	41.3	0	0	TT
12.00 - 24	STANDARD	94022557	18	8.5	8.0 ; 9.0	12.4	49	0	0	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 03:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..