

EARTHMAX SR 44 - Data Sheet



Description

EARTHMAX SR 44 is an **All Steel** radial tire suitable for a variety of applications including mining, haulage and logging applications. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) is able to optimize productivity whatever your operation is.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: On/Off Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH	ECE
7.50 R 16	STANDARD			122/118 G	6	5.5, 6.5	226	820	380	2450	TT	19		
10.00 R 20	STANDARD			146/143 G	7.50	7.0; 7.50VM; 8.0	268	1075	505	3200	TT	25		E11-54R-0015908
11.00 R 20	STANDARD	E4	***		8.00	7.50; 8.50;8.50VM	282	1111	520	3328	TT	26		
12.00 R 20	STANDARD	E4	***		8.50V	9.00V	305	1138	532	3408	TT	25		
12.00 R 24 (325/95 R 24)	STANDARD	E4	***	158 B	8.50V	9.00V	310	1250	575	3790	TT	30	140	
325/95 R 24 (12.00 R 24)	STANDARD	E4	***	158 B	8.50V	9.00V	310	1250	575	3790	TT	30	140	
325/95 R 24 (12.00 R 24)	STANDARD	E4	***	158 B	8.50V	9.00V	310	1250	575	3790	TL	30	140	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 12:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..