

# **EARTHMAX SR 475 - Data Sheet**



### **Description**

EARTHMAX SR 475 is an all steel radial tire specially designed for Rigid Dump Trucks. It is ideal for hard and rocky operations especially with long hauls. The unique tread design generate lower heat in hot climate and provides excellent traction. Its strong all steel casing and belts provide great stability and resistant to snags and punctures. EARTHMAX SR 475 has been developed with squared shoulder that ensures excellent maneuverability and handling, maximizing the ground contact.

#### **UM**

**US Standard** 

#### Construction



## Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре	Tread Depth	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94064397	E4	**	191 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	63	182
18.00 R 33	CUT RESISTANT COMPOUND	94064854	E4	***	195 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	63	182
18.00 R 33	STANDARD COMPOUND	94064861	E4	***	195 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	63	200
24.00 R 35	CUT RESISTANT COMPOUND	94066933	E4	**	209 B	17.00/3.5		25.7	85	38.2	259.4	TL	74	243
24.00 R 35	STANDARD COMPOUND	94066940	E4	**	209 B	17.00/3.5		25.7	85	38.2	259.4	TL	74	289

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 26/04/2025 12:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..