

EARTHMAX SR 49 M - Data Sheet



Description

EARTHMAX SR 49 M is an All Steel radial tire with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability. The L-4 deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to excellent resistance to rock cuts, and punctures.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader • Low Profile Dump Truck (LPDT)

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	****/****		22.00/3.0		708	1782	801	5297	TL	56	
26.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	193 B/202 A2	22.00/3.0		708	1782	801	5297	TL	56	165
26.5 R 25	CUT RESISTANT COMPOUND	L4	*	202 A2	22.00/3.0		708	1782	801	5297	TL	56	
26.5 R 25	CUT RESISTANT COMPOUND	L4	**	209 A2	22.00/3.0		708	1782	801	5297	TL	56	
26.5 R 25	CUT RESISTANT COMPOUND	SH4	****		22.00/3.0		708	1782	801	5297	TL	56	
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	****/****		25.00/3.5		780	1905	844	5600	TL	57	
29.5 R 25	CUT RESISTANT COMPOUND	L4	*	208 A2	25.00/3.5		780	1905	844	5600	TL	57	
29.5 R 25	CUT RESISTANT COMPOUND	L4	**	216 A2	25.00/3.5		780	1905	844	5600	TL	57	
29.5 R 25	CUT RESISTANT COMPOUND	E4/L4	**/*	200 B/208 A2	25.00/3.5		780	1905	844	5600	TL	57	220
29.5 R 25	CUT RESISTANT COMPOUND	SH4	****		25.00/3.5		780	1905	844	5600	TL	57	
29.5 R 29	CUT RESISTANT COMPOUND	L4	***	223 A2	25.00/3.5	24.00/3.5,26.00/3.5	786	2006	906	6320	TL	60	
29.5 R 29	CUT RESISTANT COMPOUND	SH4	****		25.00/3.5	24.00/3.5, 26.00/3.5	786	2006	906	6320	TL	60	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..