

EARTHMAX SR 49 - Data Sheet



Description

EARTHMAX SR 49 is an All Steel radial tire that has been engineered for loaders and dozers, low profile dump trucks (LPDT) and load haul dumps (LHD). EARTHMAX SR 49 provides optimum performance in severe mining operations requiring exceptional traction and stability. The tire has a directional pattern and is made of a special cut-resistant compound providing excellent durability.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader • Low Profile Dump Truck (LPDT)

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
35/65 R 33	CUT RESISTANT COMPOUND	L4	***	229 A2	28.00/3.5	--	899	2061	890	6125	TL	59
35/65 R 33	CUT RESISTANT COMPOUND	E4/L4	****/***		28.00/3.5	--	899	2061	890	6125	TL	59
35/65 R 33	CUT RESISTANT COMPOUND	L4	**	224 A2	28.00/3.5	--	899	2061	890	6125	TL	59
35/65 R 33	CUT RESISTANT COMPOUND	SH4	****		28.00/3.5	--	899	2061	890	6125	TL	59
45/65 R 45	CUT RESISTANT COMPOUND	L4	**	245 A2	36.00/4.5		1130	2730	1190	8113	TL	72

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..