



## FS 216 - Data Sheet

### Description

FS 216 has a robust log design with optimum angle and wider width to enhance traction performance for loggers and skidders. It provides excellent cut and chip resistance under the most critical operating conditions and ensures maximum protection against possible damages at any time.



### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Log Skidder

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18.4 - 26	STEEL BELTED	94027996	LS2	10	DW 16 A		18.4	58.1	26.9	174.5	TT	E11-106R-003637
23.1 - 26	STEEL BELTED	94028108	LS2	10	DW 20 A ; DW 20 B		23.1	63.6	28.6	188.2	TT	E11-106R-003650
23.1 - 26	STEEL BELTED	94029457	LS2	14	DW 20 A ; DW 20 B		23.1	63.6	28.6	188.2	TT	E11-106R-003411
23.1 - 26	STEEL BELTED	94054848	LS2	20	DW 20 A ; DW 20 B		23.1	63.6	28.6	188.2	TT	E11-106R-004635
23.1 - 26	STEEL BELTED	94040391	LS2	16	DW 20 A ; DW 20 B		23.1	63.6	28.6	188.2	TL	E11-106R-003662
23.1 - 26	STEEL BELTED	94028603	LS2	12	DW 20 A ; DW 20 B		23.1	63.6	28.6	188.2	TT	E11-106R-003651
23.1 - 26	STEEL BELTED	94031795	LS2	16	DW 20 A ; DW 20 B		23.1	63.6	28.6	188.2	TT	E11-106R-003661
28L - 26	STEEL BELTED	94049608	LS2	20	DW 25 A ; DW 25 B		28.3	65.4	29.2	193.4	TL	E11-106R-006733
28L - 26	STEEL BELTED	94057856	LS2	26	DW 25 A ; DW 25 B		28.3	65.4	29.2	193.4	TL	E11-106R-006734
28L - 26	STEEL BELTED	94029334	LS2	14	DW 25 A ; DW 25 B		28.3	65.4	29.2	193.4	TL	E11-106R-003413
28L - 26	STEEL BELTED	94031887	LS2	18	DW 25 A ; DW 25 B		28.3	65.4	29.2	193.4	TL	E11-106R-003425
18.4 - 30	STEEL BELTED	94028115	LS2	10	DW 16 A		18.4	62.1	28.5	186.5	TT	E11-106R-003638
18.4 - 30	STEEL BELTED	94029969	LS2	14	DW 16 A		18.4	62.1	28.5	186.5	TT	E11-106R-004644
24. 5 - 32	STEEL BELTED	94033669	LS2	16	DH 21	DH 21 B	24.5	72.1	32.9	214.8	TL	E11-106R-003421
30.5L - 32	STEEL BELTED	94044313	LS2	26	DH 27	DH 27 B	30.5	72.7	32.8	215.2	TL	
30.5L - 32	STEEL BELTED	94027620	LS2	16	DH 27	DH 27 B	30.5	72.7	32.8	215.2	TL	E11-106R-003426
30.5L - 32	STEEL BELTED	94028900	LS2	20	DH 27	DH 27 B	30.5	72.7	32.8	215.2	TL	E11-106R-003439
30.5L - 32	STEEL BELTED	94048397	LS2	32	DH 27	DH 27 B	30.5	72.7	32.8	215.2	TL	
DH 35.5L - 32	STEEL BELTED	94048380	LS2	30	DH 31	DH 31 H	35.7	79.2	35.9	235.9	TL	E11-106R-006503
DH 35.5L - 32	STEEL BELTED	94043729	LS2	20	DH 31	DH 31 H	35.7	79.2	35.9	235.9	TL	E11-106R-003349
DH 35.5L - 32	STEEL BELTED	94062713	LS2	24	DH 31	DH 31 H	35.7	79.2	35.9	235.9	TL	
18.4 - 34	STEEL BELTED	94028122	LS2	10	DW 16 A		18.4	66.1	30.2	198.5	TT	E11-106R-004560
18.4 - 34	STEEL BELTED	94029297	LS2	14	DW 16 A		18.4	66.1	30.2	198.5	TL	E11-106R-003401

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..