

INDUSTRIAL RIB F3 - Technical Specifications



Description

INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features an outstanding stubble-resistant compound making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 11L - 16 SL |
| LI/SS | 116 A6 |

Dimensions International Standard

| | |
|-----------------------|-----------------------|
| Ply Rating | 10 |
| Section Width (mm) | 279 |
| Overall Diameter (mm) | 830 |
| Rim Rec | W 8 L |
| Rim Alt | 8 LB ; 10 LB ; W 10 L |
| ECE | E11-106R-004304 |
| TRA Code | F3 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 3.60 |
| 30 | 1250 |
| 40 | 1120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 05:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..