



LG 306 - Data Sheet

Description

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.



UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mower • Small Tractor

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11 X 4.00 - 5	STANDARD			4	3.00 A		104	272	120	789	TL	E11-106R-004403
13 X 5.00 - 6	STANDARD			6	3.50 A		127	325	144	943	TL	E11-106R-004404
13 X 5.00 - 6	STANDARD			4	3.50 A		127	325	144	943	TL	E11-106R-003446
15 X 6.00 - 6	STANDARD			4	4.50 A		152	365	159	1059	TL	E4-106R-002174
15 X 6.00 - 6	STANDARD			6	4.50 A		152	365	159	1059	TL	E11-106R-004405
16 X 6.50 - 8	ARAMID BELTED			6	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-003499
16 X 6.50 - 8	STANDARD			8	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-004406
16 X 6.50 - 8	STANDARD			6	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E4-106R-002175
16 X 6.50 - 8	STANDARD			4	5.375 I - 55 ; I - 70 ; I - 90		170	408	182	1183	TL	E11-106R-003447
16 X 7.50 - 8	ARAMID BELTED			4	5.375 I - 55 ; I - 70 ; I - 90		178	400			TL	E11-106R-006731
18 X 8.50 - 8	ARAMID BELTED			6	7.00 I - 55 ; I - 70 ; I - 90		215	450	204	1346	TL	E11-106R-003500
18 X 8.50 - 8	STANDARD			4	7.00 I - 55 ; I - 70 ; I - 90		215	450	204	1346	TL	E11-106R-003448
18 X 8.50 - 8	STANDARD			6	7.00 I - 55 ; I - 70 ; I - 90		215	450	204	1346	TL	E11-106R-003450
18 X 9.50 - 8	ARAMID BELTED			6	7.00 I - 55 ; I - 70 ; I - 90		230	470	206	1363	TL	E11-106R-003501
18 X 9.50 - 8	STANDARD			6	7.00 I - 55 ; I - 70 ; I - 90		230	470	206	1363	TL	E4-106R-002176
18 X 9.50 - 8	STANDARD			4	7.00 I - 55 ; I - 70 ; I - 90		230	470	206	1363	TL	E11-106R-003449
20 X 10.00 - 8	ARAMID BELTED			6	8.00 I - 55	7.00 I - 55 ; I - 70 ; I - 90	254	508	221	1473	TL	E11-106R-003502
20 X 10.00 - 8	STANDARD			4	8.00 I - 55	7.00 I - 55 ; I - 70 ; I - 90	254	508	221	1473	TL	E11-106R-003451
20 X 10.00 - 8	STANDARD			6	8.00 I - 55	7.00 I - 55 ; I - 70 ; I - 90	254	508	221	1473	TL	E11-106R-003379
18 X 8.50 - 10	STANDARD			4	7.00 I - 55 ; I - 70 ; I - 90		210	460	206	1370	TL	E11-106R-003452
20 X 10.00 - 10	ARAMID BELTED			6	8.00 I - 55	7.00 I - 55	250	508	226	1473	TL	E11-106R-003503
20 X 10.00 - 10	STANDARD			6	8.00 I - 55	7.00 I - 55	250	508	226	1473	TL	E11-106R-003455
20 X 10.00 -	STANDARD			4	8.00 I - 55	7.00 I - 55	250	508	226	1473	TL	E11-

10											106R-003453	
20 X 8.00 - 10	STANDARD			4	6.00 I - 55 ; I - 70 ; I - 90	6 JA	205	500	223	1450	TL	E11-106R-003454
20 X 8.00 - 10	STANDARD			6	6.00 I - 55 ; I - 70 ; I - 90	6 JA	205	500	223	1450	TL	E11-106R-003456
23 X 10.50 - 12	ARAMID BELTED			6	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	TL	E11-106R-003580
23 X 10.50 - 12	STANDARD			6	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	TL	E4-106R-002177
23 X 10.50 - 12	STANDARD			4	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	TL	E11-106R-003352
23 X 10.50 - 12	STANDARD			8	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	TL	E4-106R-002661
23 X 10.50 - 12	STANDARD			12	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	TL	E4-106R-002665
23 X 8.50 - 12	ARAMID BELTED			6	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	TL	E11-106R-004409
23 X 8.50 - 12	STANDARD			12	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	261	1717	TL	E4-106R-002835
23 X 8.50 - 12	STANDARD			4	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	TL	E11-106R-003457
23 X 8.50 - 12	STANDARD			6	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	TL	E4-106R-002178
23 X 8.50 - 12	STANDARD			8	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	TL	E11-106R-003458
24 X 12.00 - 12	STANDARD			4	9.5 AT	9.0 AT ; 8.5 AT ; 8.0 AT	298	610	276	1774	TL	E11-106R-004407
26 X 12.00 - 12	ARAMID BELTED			6	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	TL	E11-106R-003384
26 X 12.00 - 12	ARAMID BELTED			8	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	TL	E11-106R-005304
26 X 12.00 - 12	STANDARD			8	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	TL	E4-106R-002674
26 X 12.00 - 12	STANDARD			14	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	294	1945	TL	E4-106R-002327
26 X 12.00 - 12	STANDARD			4	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	TL	E11-106R-003459
26 X 12.00 - 12	STANDARD			12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	TL	E11-106R-003524
260/55 - 12 (23 X 10.50 - 12)	IMPLEMENT	110 A8	122 A8	14	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	TL	E11-106R-006955
24 X 8.50 - 14	STANDARD			4	7 JA		210	610	280	1769	TL	E11-106R-004582
25 X 8.50 - 14	STANDARD			6	7.00 I - 55 ; I - 70 ; I - 90		220	638	294	1915	TL	E11-106R-003460
25 X 8.50 - 14	STANDARD			8	7.00 I - 55 ; I - 70 ; I - 90		220	638	294	1915	TL	E11-106R-006732
27 X 10.50 -	STANDARD			4	8.00 LB		272	705	318	2042	TL	E11-

15											106R-006848
27 X 10.50 - 15	STANDARD		12	8.00 LB		272	705	337	2055	TL	E11-106R-006849
27 X 8.50 - 15	STANDARD		4	7.00 JA		216	685	329	2076	TL	E4-106R-002204
29 X 12.50 - 15	ARAMID BELTED		10	10 LB		318	740	349	2230	TL	E11-106R-006167
31 X 15.5 - 15	ARAMID BELTED		8	13 LB		391	792	350	2313	TL	E11-106R-006735
31 X 15.5 - 15	STANDARD		4	13 LB		391	792	350	2313	TL	E11-106R-004083
31 X 15.5 - 15	STANDARD		8	13 LB		391	792	350	2313	TL	E11-106R-007115
13.6 - 16	STANDARD		4	W 12	W 11	388	975	442	2860	TL	E4-106R-002206
33 X 15.50 - 16.5	STANDARD		10	12.00		396	840	385	2538	TL	E11-106R-003004
38 X 14.00 - 20	STANDARD		4	W 11	W 11 H	375	980	447	2912	TL	E4-106R-002210
44 X 18.00 - 20	STANDARD		4	W 14 L	W 14 LH	490	1165	518	3509	TL	E11-106R-006828

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 10:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..