

## LP 450 - Technical Specifications



### Description

LP 450 is a road-oriented tire for low platforms in transport applications. This high-speed tire provides significant fuel savings as well as an extended tire life-cycle.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Low Platform Trailer

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

## Dimensions US Standard

Usa code	94008315
Ply Rating	12
Section Width (inch)	8.4
Overall Diameter (inch)	28
Static Loaded Radius (inch)	12.6
Rolling Circumference (inch)	83
Rim Rec	6.00 MH

## Load capacity (lbs)

mph / psi	100
62 LS	2835
62 LD	2490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..