

MAGLIFT LOADER - Technical Specifications



Description

MAGLIFT LOADER has been specially designed for wheel loaders operating in the most demanding applications such as demolition works, scrap metal recycling, waste transfer and mining. Indeed, the particular tread design provides excellent traction under heavy-duty service conditions, whilst the reinforced bead structure ensures best grip and eliminates any slippage risk during operations. MAGLIFT LOADER is made of an extraordinarily cut-and-chip-resistant tread compound and has a two-layer solid construction. This avoids the risk of punctures or other damage ensuring higher productivity along with an extended tire life-cycle. In addition, the sidewall geometry with specifically developed apertures provides a cushioning effect that absorbs and dampens vibrations and impacts, thus improving operator's comfort and preventing back pain. This cushioning effect also contributes to reduce equipment maintenance.

UM

International Standard

Construction

◆ SOLID

Machinery

Industrial: Loader

Version	STANDARD
Type	
Tyre Size	20.5 - 25 (525/80-25)

Dimensions International Standard

Overall Width (mm)	520
Overall Diameter (mm)	1495
Rim Rec	17.00/2.0

Load capacity (Kg)

km/h / bar	-
10	12150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..