

MP 585 - Technical Specifications



Description

MP 585 is an agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a block pattern that offers maximum stability and durability in the most difficult working conditions, also at high speeds.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Universal Vehicle

Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	10.5 - 20

Dimensions International Standard

Ply Rating	10
Section Width (mm)	273
Overall Diameter (mm)	970
Static Loaded Radius (mm)	455
Rolling Circumference (mm)	2890
Rim Rec	9
Rim Alt	9 SDC
ECE	E4-54R-0022631

Load capacity (Kg)

	km/h / bar	3.75
	90	1800
	50	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..