

MP 590 - Technical Specifications



Description

MP 590 is an agro-industrial tire suitable for loading operations with telehandlers and forklifts. This tire provides good traction and excellent stability as well as increased durability.

UM

US Standard

Construction

• BIAS

Machinery

Agriculture: Telehandler

Industrial: Forklift • Telehandler • Universal Vehicle

| | |
|-----------|------------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 18 - 22.5 (445/65 - 22.5) |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94044191 |
| Ply Rating | 20 |
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 46.9 |
| Static Loaded Radius (inch) | 20.9 |
| Rolling Circumference (inch) | 139.1 |
| Rim Rec | 14.0 |
| ECE | E11-106R-004408 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 109 |
| 25 DW | 12790 |
| 20 DW | 14330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..