

MT 612 - Technical Specifications



Description

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Industrial: Universal Vehicle

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions US Standard

Usa code	94029433
Ply Rating	20
Section Width (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	150.7
Rim Rec	10
ECE	E11-54R-0021125

Load capacity (lbs)

mph / psi	110
50 LS	10750
50 LD	9640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 06:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..