



MT 612 - Data Sheet



Description

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Trailer

Industrial: Universal Vehicle

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.00 - 20	STANDARD	94029105	18	10		15.4	49.8	23.4	150.7	TT	
14.00 - 20	STANDARD	94036585	22	10		15.4	49.8	23.4	150.7	TT	
14.00 - 20	STANDARD	94029433	20	10		15.4	49.8	23.4	150.7	TT	E11-54R-0021125
16.0/70 - 20	STANDARD	94035922	16	13.00 T		15.9	43.1	20.5	131	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..