

MULTIMAX MP 522 - Data Sheet



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
280/80 R 18 IND (10.5/80 R 18)	STANDARD	94045044	132 A8/B	W 9 ; 9 ; 9 SDC	W 8 ; W 10	11.1	35.7	16.6	108.2	TL	E11-106R-002962
340/80 R 18 IND (12.5/80 R 18)	STANDARD	94048793	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.6	18	119	TL	E4-106R-002654
340/80 R 20 IND	STANDARD	94052875	144 A8/B	11	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC	13.5	41.4	18.9	126.5	TL	E11-106R-002969
380/75 R 20 IND (14.5 R 20)	STANDARD	94045877	148 A8/B	W 12	W 11 ; 11 ; 12	15.1	42.3	19	128	TL	E11-106R-002963
400/70 R 20 IND (16.0/70 R 20)	STANDARD	94033829	149 A8/B	13	12 SDC ; 13 SDC ; 14	15.9	42	18.7	125.9	TL	E4-106R-002319
400/70 R 24 IND	STANDARD	94051403	152 A8/B	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	15.9	46.1	21	138.9	TL	E11-106R-002964
400/80 R 24 IND (16.0/80 R 24)	STANDARD	94051397	162 A8/B	DW 13	DW 12 ; DW 13 L ; DW 14 L	15.9	49.2	21.8	148.7	TL	E11-106R-002965
440/80 R 24 IND	STANDARD	94052257	161 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.4	51.7	23.1	155.8	TL	E11-106R-002966
460/70 R 24 IND (17.5L R 24)	STANDARD	94031313	159 A8/B	DW 15 L	DW 14 L ; DW 16 L	18.3	49.2	22.4	148.3	TL	E4-106R-002396
500/70 R 24 IND (19.5L R 24)	STANDARD	94032686	164 A8/B	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.4	155.1	TL	E4-106R-002395
540/70 R 24 IND	STANDARD	94052264	168 A8/B	DW 16 L	DW 18 L	20.9	53.8	24.1	162.7	TL	E11-106R-002967
480/80 R 26 IND	STANDARD	94073108	167 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.1	168.8	TL	E11-106R-008146
480/80 R 26 IND	STANDARD	94052707	160 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.1	168.8	TL	E11-106R-002970
440/80 R 28 IND	STANDARD	94052240	156 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.4	55.7	25.3	168.4	TL	E11-106R-002968

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..