

RIB 774 (C) - Technical Specifications



Description

RIB 774 (C) is a low-section and narrow-width implement tire. It is ideal for hay harvesting and transport applications with balers and trailers, both on- and off-the-road. It features great load capacity and a long tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Trailer

Version	STANDARD
Type	TL
Tyre Size	225/75 - 17.5
LI/SS FREE ROLLING	134 A8

Dimensions US Standard

Usa code	94011025
Ply Rating	12
Section Width (inch)	8.7
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	90.9
Rim Rec	6.75
ECE	E11-106R-004657

Load capacity (lbs)

mph / psi	100
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 22:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..