



RIB 900 - Data Sheet

Description

RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire life-cycle.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer



SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	STANDARD	94026357	139 A8	10	AG 13.00		15.9	34.4	15	100.9	TL	
400/60 - 15.5	STANDARD	94026173	145 A8	14	AG 13.00		15.9	34.4	15	100.9	TL	E4-106R-001551
400/60 - 15.5	STANDARD	94026340	147 A8	16	AG 13.00		15.9	34.4	15	100.9	TL	E4-106R-001548

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 22:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..