

# **ROCK GRIP IND4 (ECH) - Technical Specifications**



### **Description**

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) is a bias-ply tire designed for Empty container handler in several applications including industrial handling and steelworks. The special ROCK GRIP compound ensure particular heat resistance along with great stability and durability.

#### **UM**

International Standard

#### Construction



### Machinery

Industrial: Empty Container Handler

Version	PORT INDUSTRIAL
Туре	TL
Tyre Size	16.00 - 25

### **Dimensions International Standard**

Ply Rating	32
Overall Width (mm)	470
Overall Diameter (mm)	1525
Static Loaded Radius (mm)	699
Rolling Circumference (mm)	4514
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	16875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 29/04/2025 14:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..