

ROCK STAR L4 - Technical Specifications



Description

ROCK STAR LOADER has been specifically designed for cranes and loaders. In addition to excellent traction, the unique tread compound provides superior cut and chip resistance. ROCK STAR LOADER is a 24-ply-rated tire ensuring outstanding load capacity and extraordinary durability.

UM

US Standard

Construction



Machinery

Industrial: Loader

Version	STANDARD
Туре	ΤΤ
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94058211
Ply Rating	24
ТМРН	1
Overall Width (inch)	15.4
Overall Diameter (inch)	56.1
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	L4

Load capacity (lbs)

mph / psi	123
5	20940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 05:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..