



## SKID POWER ( CHEVRON ) - Data Sheet



### Description

SKID POWER (CHEVRON) has been specially designed for skid steers in construction applications. It features excellent traction as well as enhanced self-cleaning properties. SKID POWER (CHEVRON) is particularly suitable for loose surfaces and shows high cut and chip resistance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Skid Steer

| SIZE      | Version   | LI/SS  | PR | RIM REC | RIM ALT | SW  | OD  | SLR | RC   | Type | ECE             |
|-----------|-----------|--------|----|---------|---------|-----|-----|-----|------|------|-----------------|
| 7.00 - 15 | IMPLEMENT | 106 A8 | 6  | 5.50 F  | 6 LB    | 203 | 762 | 347 | 2295 | TL   | E11-106R-003583 |
| 7.00 - 15 | STANDARD  |        | 6  | 5.50 F  | 6 LB    | 203 | 762 | 347 | 2295 | TL   |                 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 01:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..