

## SKID POWER - Technical Specifications



### Description

SKID POWER has been designed for skid steers in construction applications. It shows excellent traction as well as enhanced self-cleaning features. The tire features an extra deep tread along with extra sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER is the ideal tire for loose surfaces.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	25 X 8.5 - 14
LI/SS	106 A2

## Dimensions US Standard

Usa code	94042050
Ply Rating	6
Section Width (inch)	8.4
Overall Diameter (inch)	25.7
Static Loaded Radius (inch)	12
Rolling Circumference (inch)	75.3
Rim Rec	7 JA
ECE	E11-106R-006265

## Load capacity (lbs)

mph / psi	50
5	2130
10	1680
15	1555

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..