

# **STAR TRAC - Technical Specifications**



# **Description**

STAR TRAC is the BKT tire for harvesters at cotton farms, which is able to support heavy loads. Thanks to its particularly deep tread design, it ensures both excellent traction in the fields and excellent performance during road transfers. On cotton plantations showing the typical middle-sized shrubs, harvesting demands tire features like excellent flotation and reduced soil compaction. Moreover, the tire is made of a special compound providing high resistance against cuts and typical damages of this application.

#### **UM**

International Standard

#### Construction



# Machinery

Agriculture: Cotton Picker

Version	STANDARD
Туре	TL
Tyre Size	DW 500/95 D 32
LI/SS	162 A8/169 A5

# **Dimensions International Standard**

Section Width (mm)	500
Overall Diameter (mm)	1836
Static Loaded Radius (mm)	809
Rolling Circumference (mm)	5324
Rim Rec	13.00 DW

# Load capacity (Kg)

km/h / bar	1.70
40	4750
25	5800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 26/04/2025 13:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..