

TR 138 - Data Sheet



Description

TR 138 has been specially designed for telehandlers and backhoe loaders in agriculture. It is best suitable for soil tillage and spraying applications. Excellent traction on soft soil, best self-cleaning properties and stability are key features which make the TR 138 tire the ideal partner even with difficult ground conditions.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Backhoe Loader • Telehandler

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
17.5L - 24	STANDARD	94061877	151 A8	12	DW 15L	DW 14L	17.7	50.8	22.7	151	TL	E11-106R-005232

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 12:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..