

## TR 144 - Technical Specifications



### Description

TR 144 is suitable to equip small tractors to be used in soil tillage operations. TR 144 ensures outstanding performance in all operating conditions which require excellent traction with high loads. It is also available in a "special" version, which is best suitable for heavy-duty service.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Small Tractor

Version	STANDARD
Type	TL
Tyre Size	9.5 - 16
LI/SS	99 A8

Dimensions US Standard

Usa code	94053568
Ply Rating	8
Section Width (inch)	9.6
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	100.7
Rim Rec	W 8 L
Rim Alt	8 LB
ECE	E11-106R-004327
TRA Code	R1

Load capacity (lbs)

mph / psi	42
25	1710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 01:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..