

## TR 145 - Data Sheet



### Description

TR 145 has been specifically designed for small tractors. The special tread pattern provides excellent traction and outstanding self-cleaning properties. The wide and deep lug design ensures an extended tire service life. The TR 145 tire has a large contact area which offers excellent driving comfort and high directional stability.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Small Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
160/90 - 12	STANDARD	94062744	R1	72 A8	6	4.00		6.3	24.8	11.6	77.5	TT	E11-106R-005854

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 01:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..