

TR 390 - Technical Specifications



Description

TR 390 is an agro-industrial tire suitable for sugar cane trailers and compactors. TR 390 features high load capacity and increased durability. Its "dual bead HD" version is particularly suitable for industrial tractors and transport operations using trailers, whereas its "dual bead HD special" version is ideal for heavy-duty service.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Industrial: Compactor

| | |
|-----------|--------------|
| Version | DUAL BEAD HD |
| Type | TL |
| Tyre Size | 28L - 26 |
| LI/SS | 172 A6 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 20 |
| Section Width (mm) | 714 |
| Overall Diameter (mm) | 1560 |
| Static Loaded Radius (mm) | 690 |
| Rolling Circumference (mm) | 4545 |
| Rim Rec | DW 25 B |
| Rim Alt | DW 23 B |
| ECE | E11-106R-004609 |
| TRA Code | R3 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 2.80 |
| 30 | 6300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..