

TR 678 - Technical Specifications



Description

TR 678 has been specially designed for forestry applications. Its robust lug design provides excellent traction and self-cleaning. The strong casing structure stands for high load capacity whereas its steel belts protect the tire from punctures and damages. TR 678 features a cut-resistant tread compound providing excellent cut-andchip resistance even on difficult terrains under extreme conditions.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery • Trailer Industrial: Excavator • Trailer

Version	STEEL BELTED
Туре	TL
Tyre Size	780/50 - 28.5
LI/SS	190 A2/ 182 A8

Dimensions International Standard

Ply Rating	24
Section Width (mm)	770
Overall Diameter (mm)	1515
Rim Rec	AG 26.00
ECE	E11-106R-006975
TRA Code	LS2

Load capacity (Kg)

km/h / bar	6.00
40	8500
10	10600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 09:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..