

## AGRIMAX ELOS - Especificaciones técnicas



### Description

AGRIMAX ELOS ha sido proyectado para ofrecer la máxima tracción en condiciones de uso particularmente problemáticas en terrenos mojados - como por ejemplo los arrozales - y pantanosos. El dibujo de la banda de rodadura ha sido estudiado para garantizar óptimas cualidades de auto-limpieza, esenciales en los trabajos realizados en terrenos fangosos y durante los desplazamientos. Para optimizar la productividad de la empresa agrícola, en el dibujo del neumático AGRIMAX ELOS se han integrado unas protecciones en los flancos para asegurar la máxima protección ante posibles daños.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	520/85 R 46
LI/SS	169 A8/169 B

## Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	2075
Static Loaded Radius (mm)	957
Rolling Circumference (mm)	6293
SRI (mm)	975
Rim Rec	DW 16 L
Rim Alt	DW 15 L ;DW 18 L; W 15 L ; W 16 L; W18 L; DD 16 L ; DD 18 L
ECE	E11-106R-007935
TRA Code	R2

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	2265	2670	3075	3425	3830	4180	4585	5050	5455	5800
40	2265	2670	3075	3425	3830	4180	4585	5050	5455	5800
30	2425	2860	3295	3665	4100	4475	4910	5405	5840	6210
10 LT	3035	3580	4125	4590	5135	5600	6145	6765	7310	7775
10 HT	2425	2860	3295	3665	4100	4475	4910	5405	5840	6210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..