

AGRIMAX FORTIS - Especificaciones técnicas



Description

AGRIMAX FORTIS es vuestro compañero más fiable para todas las operaciones de preparación y tratamiento del terreno y de transporte. Diseñado para equipar los tractores más potentes de última generación, AGRIMAX FORTIS permite transportar cargas muy elevadas con velocidades hasta 65 km/h. Asegura una tracción excelente además de una manutención superior y un gran confort para una experiencia perfecta de conducción. El neumático ha sido desarrollado con una carcasa reforzada de nylon que mejora la productividad en los campos y preserva el suelo gracias a una menor compactación.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	800/70 R 38
LI/SS	178 D/181 A8

Dimensions US Standard

Usa code	94032969
Section Width (inch)	31.4
Overall Diameter (inch)	82.1
Static Loaded Radius (inch)	35.9
Rolling Circumference (inch)	244.2
Rim Rec	DW 25 B
Rim Alt	DW 27 B
ECE	E4-106R-001424
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	7940	9260	10420	11570	12730	13720	15210	16500
30	8330	9720	10950	12160	13370	14420	15970	17360
25	8730	10180	11460	12730	14010	15100	16730	18190
20	9130	10650	11980	13320	14650	15780	17490	19010
5 LT	10640	12410	13970	15510	17060	18400	20390	22160
5 HT	9130	10650	11980	13320	14650	15780	17490	19010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 3:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..