

AGRIMAX RT 657 - Especificaciones técnicas



Description

AGRIMAX RT 657 es el neumático ideal para utilizarlo tanto en el laboreo del suelo como por la carretera; además algunos tamaños también son adecuados para la vendimia. Este neumático asegura un excelente confort en la conducción, así como significativos ahorros de carburante. Presenta una elevada capacidad de carga a altas velocidades. AGRIMAX RT 657 es la mejor elección para quien necesite un neumático versátil y fiable sin comprometer las prestaciones.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	320/65 R 18
LI/SS	109 A8/B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	873
Static Loaded Radius (mm)	392
Rolling Circumference (mm)	2587
SRI (mm)	425
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-000636
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	600	695	785	870	950	1030
40	600	695	785	870	950	1030
30	645	745	840	930	1020	1105
10 LT	805	930	1055	1165	1275	1385
10 HT	645	745	840	930	1020	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..