

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

US Standard

Construction



RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	280/70 R 20
LI/SS	116 A8/B

Dimensions US Standard

Usa code	94044238
Section Width (inch)	10.8
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	106.5
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-00641
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1300	1490	1710	1930	2150	2370	2570	2760
25	1300	1490	1710	1930	2150	2370	2570	2760
20	1390	1600	1840	2070	2310	2550	2760	2950
5 LT	1740	2000	2290	2590	2890	3190	3440	3690
5 HT	1390	1600	1840	2070	2310	2550	2760	2950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 5:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..