

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

International Standard

Construction



RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	420/70 R 30
LI/SS	134 D

Dimensions International Standard

Section Width (mm)	418
Overall Diameter (mm)	1398
Static Loaded Radius (mm)	631
Rolling Circumference (mm)	4172
SRI (mm)	675
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-005830
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1170	1360	1550	1740	1930	2120
50	1230	1430	1630	1830	2030	2230
40	1280	1490	1700	1910	2120	2325
30	1345	1565	1785	2005	2225	2440
10 LT	1565	1825	2080	2335	2590	2845
10 HT	1345	1565	1785	2005	2225	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..