

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

International Standard

Construction



RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	620/70 R 42
LI/SS	166 D

Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1935
Static Loaded Radius (mm)	876
Rolling Circumference (mm)	5801
SRI (mm)	925
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005998
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2495	2865	3290	3710	4135	4560	4985	5300
50	2620	3010	3455	3900	4345	4790	5235	5565
40	2730	3135	3600	4065	4530	4995	5460	5805
30	2865	3295	3780	4270	4755	5245	5730	6095
10 LT	3340	3840	4410	4975	5545	6115	6680	7105
10 HT	2865	3295	3780	4270	4755	5245	5730	6095

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 0:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..